

Contents

- Features
- Specifications

Highlights

2.8" LCD

3000 Fingerprints

120000 Logs

With Mifare card
or EM Card



Features

- Best Quality Algorithm with great identification speed within 1 second.
- Professional design for easy installation.
- Large-screen color LCD display, 2.8" inch TFT high-definition graphical interface, a graphical interface can show color photographs of staff.
- Identification of a variety of modes to meet the individual needs of user's fingerprints, the password can be any combination of recognition.
- Off-line function for inconvenient network and USB-disk can upload and download files and images.
- Embedded IP protocol and 100M high-speed network.
- The Time Attendance can speak and have all kinds of voice prompt and read the number of staff.
- Many complementary functions: notice, birthday wishes, gives the correct time, advertising and so on.
- Storage capacity can be dynamically allocated.
- Advanced embedded WinCE operating system
- Can connect to an external Wiegand 26/34, double readers can be formed to work simultaneously.
- Unique work of the six models: 16 function keys and six keys to work, can effectively distinguish between on-duty, off-duty, out, out-back, overtime, off-overtime.
- A variety of modes of communications: RJ45, U-Disk and so on.

Specifications

- Modes of identification: Mifare one card /proximity card, fingerprint and password
- Speed: RFID < 0.7 seconds / Fingerprint Identification < 1 second
- Distance: 2.5-10 cm (Mifare one card), 2.5-15cm (proximity card).
- bytes of one fingerprint: 1668 Byte
- 3000 Fingerprint storage
- 120000 Logs storage
- FAR: <0.0001%
- FRR: <0.01%
- LCD: 2.8-inch true color, 640 x 480 Pixels
- Network port: 100/10Base-T Ethernet
- Communication: RS232 or RS485 or TCP/IP or Wiegand or U-Disk
- Card Reader : Mifare one or Proximity Card
- Access Control Function: Single embedded controller(standard)
- USB port: Embedded USB2.0 High Speed Interface
- USB disk transmission:
- USB disk storage attendance record, upload download files
- Sound effect: Voice and bell regularly
- Power: 25W AC110V 50HZ ±15% voltage
- Environment: 0 to -50 C temperature and humidity 10%-90%
- Exterior dimensions : 380X280X140(mm),3Kg