

Contents

- Features
- Specifications
- Kit Contents
- Ordering Instructions

Highlights

3000 User Capacity

60000 Transactions

RS232/RS485, TCP/IP, USB

Optional Mifare/Proximity Card

Mantra Softech
(India) Pvt Ltd
www.mantratec.com



Features

- Color LCD screen
- FAR is less than 0.00001%
- FRR is less than 0.001%
- User capacity is 3,000 expendable to 30,000
- Transaction capacity is 60,000
- Identification speed is less than 1 second
- Scratchproof Optical sensor
- Supports multiple languages
- High Quality voice
- Optional Mifare/Proximity Card
- 360 Degree Fingerprint rotation

Specifications

- RS232/RS485, TCP/IP Communication Options
- Optional Proximity/Mifare options
- Optional inbuilt battery option
- Optional Access Control Feature
- Optional USB port for direct PC Connectivity
- USB Pen Drive Backup Options
- Identification mode: Fingerprint, Fingerprint + Card, Fingerprint + P/W

- Anti Static < 15V
- Operating humidity : 0 Deg to 45 Deg C
- Power Consumption < 5W
- Optional Weigand input/output

Kit Contents

- Terminal
- CD
- Manual
- Power Adapter

Ordering Instructions

Features	BioTime6
USB Port for Data Download	Inbuilt
USB port for PC Connectivity	U
TCP/IP	T
Battery	B
Proximity Card	C
Mifare Card	M
Access Control	A

Example:

BioTime7 with TCP-IP, USB and Battery is **BioTime7-TUB**