

BioTime3



❖ Description

BioTIME3 is a standalone fingerprint T&A system, designed specially for large middle corporate and industries. The identification speed is fast and FFR and FAR are low. Memory stick solves the problem of no PC in local site. You just download records into the stick and take it to where there is PC. Could update its software with windows serve SQL for deal with plenty of datum.

❖ Features

- ▶ Algorithms with dependability and accuracy, identification speed obviously improved, process 1000 Fingerprint.
- ▶ Identification time within 0.7 second.
- ▶ Alarm for invalid time attendance and repetitious.
- ▶ Be equipped with system of calendar and is on an equal footing with PC.
- ▶ Sensor window cotton improves image quality, accepts dry, wet fingers.
- ▶ Adjust image distortion, assure fingerprint matching consistency.
- ▶ Inbuilt proximity card feature.

❖ Technical Parameters

User capacity	: 1,000
Transaction Storage:	: 30,000
Period of data:	: keep data for 3 years when no current.
RS232 Baud rate:	: port rate(9600BPS,19200BPS,38400BPS)
Verification mode:	: 1:1,1:N
FAR:	: <0.00001%
FRR:	: <0.001%

❖ Technical Parameters

Response time:	: <0.7 second
Alarm clock:	: 24 kinds (embedded music alarm), circulate, Input the signal of alarm
Communication:	: RS232 or RS485 or TCP/IP or MODEM
Card Reader	: Proximity Card
Network Mode:	: 31 units (RS485 mode), 542 units (TCP/IP), 255 units (Modem)
Distance:	: 1200m (RS485), unlimited (TCP/IP, Modem)
Access control	: support nine sections of time control
Display:	: English, time, ID number, Name
Working mode:	: time & attendance, standalone, can working persistently, electronic lock, alarm lock, alarm indicator light
Time & Attendance mode	: fingerprint and password
Save function:	: turn off device automatically for saving
Size:	: 195*55*130mm
Power:	: AC 100 to 240 V 50 to 60 Hz(<12W)
Warrant of period:	: 12 months.
Temperature and humidity	: 0 - 45,20%-80%
Applications:	: Factory/office/bank/hotel etc.