# MANTRA

# MT100

# **Biometric Terminal**

### **Ultimate Terminal for Management Solutions**

Mantra Softech is a Global Hi-Tech Manufacturer of Biometric Products and Solutions. We offer a Wide Range of Products in Biometric and RFID Industry.



MANTRA




# Introduction

Mantra MT100 is with IRIS and Fingerprint Terminal, developed based on the latest biometric technology. The use of an IRIS and fingerprint biometrics makes it more secure for any transaction and helps to increase the overall operational efficiency of the business.

The MT100 biometric terminal runs on the Android operating system and is powered by an ARM Cortex A53 @2.0 GHz quad-core processor. It also includes 2 GB of RAM and 32GB of flash memory. The device supports an external keyboard, which can be connected through a USB or Bluetooth interface. The device is designed to accommodate the rising use of biometric authentication with an STQC-certified fingerprint and IRIS sensor.

### Main Features



MANTRA

# Ultimate Terminal for Management Solutions

# Specification



# Hardware & System

Memory
Operating System
QR & Barcode Scanner
Audio
Control Buttons
Dimensions (in mm)

: ARM Cortex A53 @2.0 GHz Quad Core Processor : 2GB RAM + 32GB eMMC : Android 13 : 8MP AF camera with High brightness Flash LED : High-Quality 1W Speaker for Announcements : 1x Power On/Off, 1x Reset Key : 237 x 236 x 87mm



#### Display & Touch

Display Touch : 7" IPS LCD with resolution (1024 X 600) with 16M colors : Scratch Resistant Multi-Point Capacitive Touch Screen with 6H Toughen Glass



#### **IRIS Scanner (Optional)**

: > 50% @ 1.0 LP/mm
: > 10 Pixels/mm
:>= 0.6x IRIS Radius
:>= 0.2x IRIS Radius
: 700-900 nm
: 8 Bits/Pixel
: CE, FCC, RoHS, BIS, IP54, STQC L0, IEC 62471



#### **Fingerprint Sensor**

Fingerprint Type	: Scratch Free Optical FAP10 Sensor
Fingerprint Image	: 276 x 336 Pixels ( Platen Area: 14.0 mm x 17.0 mm)
Image Specs	: 500DPI, 8 Bit Grayscale
Certifications	: CE, FCC, RoHS, STQC L1, FBI PIV, EN/IEC 62368-1 , IS13252 Part I



### **Ultimate Terminal for Management Solutions**

# Specification



#### **Thermal Printer**

Printer
Printing Speed
Effective Printing Width
Style

: Integrated 2" Thermal Printer : 70mm/s : 48mm : Black and White



#### Sensor

Accelerometer		
Other Sensor		

: 3-AXIS Accelerometer : Ambient Light Sensor



#### Electrical Power Adapter

Battery
Charging Connector
Input Power

: Input: 90 to 275V AC , 50Hz. with surge protection Output: 5V, 3A DC : Swappable & Rechargeable 8940mAH Li-on battery : DC Jack : 5V, 3A DC



#### Interface

Interface	
4G/3G/2G	: 2G GSM/GPRS/EDGE: 850/900/1800/1900
	3G WCDMA: B1/B2/B5/B8
	4G FDD: B1/B3/B5/B7/B8/B38/B40/B41
	4G TDD: All Band
	(Optional: External Antenna)
SD Card	: Micro SD slot supporting up to 256 GB memory card
Wi-Fi 2.4GHz & 5.0 Ghz	: IEEE 802.11 a/b/g/n/ac with Flex antenna
Ethernet 10/100 Mbps (Optional)	: Ethernet 10/100 Mbps
Bluetooth	: BT & Bluetooth 5.1, 16DB Power TX Capacity
GPS	: 16 Channel NMEA Compliant with Flex Antenna, AGPS Supported
SIM Slot	: 2 x Micro SIM Slot
SAM Slot	: 2 x SAM Slot
Micro USB	: 1 x Micro USB Port for PC Connection as debug port
USB	: 2 x USB2.0 Type A



#### Environmental

Operating Temperature	: 0°C to +50°C
Storage Temperature	: - 20°C to +85°C
Humidity (Operating / Storage)	: < 90% RH, Non-condensing



#### Certifications

Certifications

: CE, FCC, RoHS, BIS, IP54





www.mantratec.com



